

ProDAQ LXI Data Acquisition Systems

ProDAQ 8036 LXI Trigger Bus Cable



OVERVIEW

The ProDAQ 8036 LXI trigger bus cable connects the ProDAQ 6100 LXI function card carrier or the 3030 PCI Express VXIbus slot-0 interface to any device equipped with LXI triggers.

The robust, shielded cable and the die-cast connectors ensure a stable connection and prevent accidental disconnects.

LXI

Features & Benefits

- ▶ **Cable for** ProDAQ 6100 and ProDAQ 3030
- ▶ Robust shielded cable
- ▶ **Support for links** up to 7m (22.97 ft.)

For more information, visit www.bustec.com.

Learn more about the **ProDAQ 8036** on our website by scanning the code below.





SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Compatibility	LXI Class A
Length	Up to 7m (22.97 ft.)
Cable Type	Copper, Shielded, Round
Connectors	Compatible with LXI trigger cabling standard

ENVIRONMENTAL

Temperature	0°C to +70°C (operational) -40°C to +70°C (storage only)
Humidity	10% - 90% (non-condensing)

WARRANTY PERIOD

12 months (extended periods available at additional cost)

Ordering Information

- ▶ **8036-xx** LXI trigger bus cable

Length

(Custom length available)

- ▶ **8036-AB**, 0.5m
- ▶ **8036-AC**, 1m
- ▶ **8036-AD**, 2m

Related Products

- ▶ **6100-xx** LXI Function Card Carrier
- ▶ **3030-Ax** PCI Express VXIbus Slot-0 Interface
- ▶ **8037-AA** LXI Trigger Bus Termination

Contact Bustec

- ▶ **Europe**
Bustec Ltd.
Bustec House
Shannon, Co. Clare
Ireland

T +353 61 707 100
F +353 61 707 106
E sales@bustec.com

- ▶ **North America**
Bustec, Inc.
1507 East Valley Parkway
Suite 3-412
Escondido, CA 92027
U.S.A.

T 909. 797.0484
F 760. 751.1284
E sales@bustec.com